


Keystone Capping




Keystone Capping Straight-Face



	DIMENSIONS (MM)	DIMENSIONS (IN)
	102 x 267 x 432	4 x 10 1/2 x 17
Weight/unit	30 kg	64 lb
Units/length	2.20 units/lin. m	0.67 units/ft lin.
Area/cube	2.60 m ²	28.00 ft ²
Qty/cube	56 units 7 Rows	56 units
Weight/cube	1655 kg	3640 lb

CODE	COLOUR
16054730	Smoke Grey

TYPICAL ROW




TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Keystone Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

For additional details see our landscaping installation guide on our website.

Keystone Wall




Keystone Wall - Compact Straight-Face



	DIMENSIONS (MM)	DIMENSIONS (IN)
	204 x 305 x 457	8 x 12 x 18
Weight/unit	45 kg	99 lb
Units/surface	10.80 units/m ²	1.00 units/ft ²
Area/cube	3.70 m ²	40.00 ft ²
Qty/cube	40 units 5 Rows	40 units
Weight/cube	1832 kg	4031 lb

CODE	COLOUR
16055000	Smoke Grey

TYPICAL ROW




Keystone Wall Corner




	DIMENSIONS (MM)	DIMENSIONS (IN)
	204 x 230 x 457	8 x 9 x 18 13/16
Weight/unit	52 kg	114 lb
Units/surface	7.20 units/m ²	0.67 units/ft ²
Area/cube	2.79 m ²	30.00 ft ²
Qty/cube	20 units 2 Rows	20 units
Weight/cube	1044 kg	2296 lb

CODE	COLOUR
16052390	Smoke Grey

TYPICAL ROW



LAYING PATTERN



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Keystone Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Application: Supporting walls
For additional details see our landscaping installation guide on our website.