









Capio Paver *New*




	Dimensions mm	Dimensions po	Code	Colour	Typical Row	
A 	A	60 x 152 x 102		Prestige		
	B	60 x 152 x 152	2 3/8 x 6 x 4	127001183		Range Amber Beige
B 	C	60 x 152 x 203	2 3/8 x 6 x 6	127001181		Range Scandina Grey
	D	60 x 152 x 254	2 3/8 x 6 x 8	127001182		Rockland Black
C 	E	60 x 152 x 305	2 3/8 x 6 x 10	Sold in full cubes Production location Montreal		
	Weight/unit	4 kg	9 lb			
D 	Unit/area (avg.)	0.03 unit/m ²	0.33 unit/ft ²			
	Area/layer (avg.)	1.07 m ²	11.5 ft ²			
E 	Area/cube	10.7 m²	10 Rows	115 ft²		
	Qty/cube	A=80 B=80 C=80 D=60 E=60				
	Weight/cube	1467 kg	3234 lb			

Laying Pattern



Linear

 1 bag of sand covers approx. 108 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Capio Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.