## Mega Melville® Slab















	Dimension	s mm	Dimensions in.		
	60 x 570 x 950		2 3/8 x 22 7/16 x 37 3/8		
Weight/unit	79 kg		175 lb		
Area/unit	0.54 m <sup>2</sup>		5.83 ft <sup>2</sup>		
Area/layer	1.08 m <sup>2</sup>		11.56 ft <sup>2</sup>		
Area/cube	9.72 m²	9 Rows	104.94 ft²		
Qty/cube	18 units		18 units		
Weight/cube	1422 kg		3150 lb		


Code	Colour	Typical Row			
	Prestige				
12053566	Range Amber Beige				
12052363	Range Margaux Beige	_			
12052772	Range Chambord Grey	_			
12052362	Range Scandina Grey				
12052360	Rockland Black	_			
	Standard	_			
12053565	Range Shaded Grey				
12052366	Range Newport Grey				
		_			

Sold in full cubes only Production location Cambridge

## **Laying Patterns**







Modular 83% Melville 60 17% Mega Melville 60

## ○ Techniseal 1 bag of sand covers approx. 289 ft²

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mega Melville Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

 $<sup>^{\</sup>star}$  Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).