Metrik™ Slab

smooth

	Dimensions mm		Dimensions in.
	60 x 70 x 280		2 3/8 x 2 3/4 x 11
Weight/unit	2.7 kg		5.96 lb
Area/unit	0.02 m²		0.21 ft²
Area/layer	0.92 m²		9.95 ft²
Area/cube	**11.09 m²**	**12 Rows**	**119.40 ft²**
Qty/cube	576 units		576 units
Weight/cube	1558 kg		3434 lb

Code	Colour
	Prestige
10502884	Blizzard (2)
10502882	Rockland Black (1)
127000940	Range Scandina Grey (1) - N

Sold in full cubes only
Can be double stacked
Production locations:
Cambridge (1)
Montreal (2)

Typical Row



Laying Patterns



Checkerboard



Offset 1/2



Offset 1/3



Herringbone

Techniseal 1 bag of sand covers approx. 55 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Metrik Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.