




Mondrian® Plus 80 Small Rectangle Paver




	Dimensions mm	Dimensions in.	Code	Colour	<div>Typical Row</div> <div></div>	
	80 x 165 x 330	3 1/8 x 6 1/2 x 13		Prestige		
	Weight/unit	10 kg	22 lb	10550516		Rockland Black
	Unit/area	18.52 units/m²	1.71 units/ft²	Sold in full cubes only		
	Area/layer	0.82 m²	8.79 ft²	Production location Bolton		
	Area/cube	7.38 m²	9 Rows	79.11 ft²		
	Length/row	4.95 lin. m	16.25 lin. ft			
	Length/cube	59.43 lin. m	195.00 lin. ft			
	Qty/cube	135 units	135 units			
	Weight/cube	1400 kg	3086 lb			

Laying Patterns



Linear



Herringbone

Techniseal 1 bag of sand covers approx. 29 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 80 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).