



Vertex Slab *New*




	Dimensions mm	Dimensions in.
A	60 x 200 and 302 x 610	2 3/8 x 7 7/8 and 11 7/8 x 24
Weight/unit	39 kg	85 lb
B		
Area/unit	0.153 m ²	1.65 ft ²
Area/layer	1.22 m ²	13.17 ft ²
Area/cube	12.2 m²	131.7 ft²
Qty/cube	80 units	80 units
Weight/cube	1725 kg	3803 lb

Code	Colour
	Prestige
127001178	Range Amber Beige
127001179	Range Scandinavia Grey
Sold in full cubes only	
Production location Montreal	




Laying Patterns



Stack Bond



Arrows



Lines of Capio Paver



Rows with Melville 24 x 24 Slab

1 bag of sand covers approx. 181 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vertex Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.