



Wallstone® Wall




Standard	Dimensions mm	Dimensions in.
	100 x 200 x 300	3 15/16 x 7 7/8 x 11 13/16
Weight/unit	13.3 kg	29.3 lb
Unit/area	-	3.10 units/ft ²
Area/cube	-	34.80 ft ²
Length/cube	-	106.30 lin. ft
Qty/cube	108 units	108 units
Weight/cube	1436 kg	3165 lb

Code	Colour
	Standard
16259322	Desert Grey Blend
16259323	Granite Blend
Sold by - 36 pieces	
Split charges apply	
Production location Cambridge	


Typical Row




Corner/ Column	Dimensions mm	Dimensions in.
	100 x 200 x 300	3 15/16 x 7 7/8 x 11 13/16
Weight/unit	13.10 kg	28.90 lb
Unit/area	-	0.54 ft ²
Qty/cube	36 units	36 units
Weight/cube	595 kg	1312 lb

Code	Colour
	Standard
16259316	Desert Grey Blend
16259317	Granite Blend
Sold by piece	
Split charges apply	
Production location Cambridge	


Typical Row



Laying Patterns



PATTERN 1: WALL ART 1
Place Wallstone standard units vertically and horizontally to create interesting patterns within the wall.



PATTERN 2: WALL ART 2
Add an additional dimension to your wall by including Wedgestone wall units in your pattern (shaded). Consider recessing blocks to add further distinction. Except for the coping course, it is not recommended to set units forward beyond the front of the base course.

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wallstone Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Applications: Retaining walls MAX 10 m (3.3 ft)


Additional details: See our landscaping installation guide on our website.



Wallstone and Wedgestone Wall can be used separately or in combination for greater flexibility.

Features: Suitable for gravity or grid, vertical or setback, straight or curved walls. All Wallstone Wall units come pre-split. End grooves on Wallstone Standard Units maintain interlock between courses, even when placed vertically. 2/3 of Standard Units are also double rock-faced.

Tips: Patterned Wallstone walls can be stacked vertically up to 6 courses high.

Wallstone 12 inch Capping





	Dimensions mm	Dimensions in.	Code	Colour	Typical Row	
	100 x 200 x 300	3 15/16 x 7 7/8 x 11 13/16		Standard		
	Weight/unit	13.10 kg	28.90 lb	16259305		Desert Grey Blend
	Units/length	-	3.1 units/ft²	16259306		Granite Blend
	Length/row	-	106.30 lin. ft	Sold by 18 pieces		
	Qty/cube	108 units	108 units	Split charges apply		
	Weight/cube	1433 kg	3159 lb	Production location Cambridge		


TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wallstone 12-inch Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width : ±3.2 mm Height: ±3.2 mm

Wedgestone Capping



	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	100 x 200 x 231 / 153	3 15/16 x 7 7/8 x 9 3/32 / 6		Standard	
	Weight/unit	8.35 kg	18.40 lb	16259328	Desert Grey Blend
	Length/cube	–	113.60 lin. ft	16259329	Granite Blend
	Qty/cube	150 units	150 units	Sold by 25 pieces	
	Weight/cube	1390 kg	3064 lb	Split charges apply Production location Cambridge	



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wedgestone Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width : ±3.2 mm Height: ±3.2 mm