## **Boulevard Drain** Paver

=

textured

Beige - Smooth

smooth



Colour						
$\Gamma_{-}$	White - Smooth					
	Cinder Grey - Smooth					
	Charcoal - Smooth					
	Light Charcoal - Smooth					
	Black ETX - Smooth					
	Light Grey - Smooth					
	Beige Grey - Smooth					

Å

S

Colour			
Cinder Grey - Granitech			
Light Charcoal - Granitech			
Charcoal - Granitech			
Light Grey - Granitech			
Beige Grey - Granitech			
Beige - Granitech			
Opal White - Granitech			
Stanstead Grey - Granitech			
Cambrian Brown - Granitech			
Cambrian Black - Granitech			



209 x 209		Dimensions mm	Dimensions				Typical Row	
		100 x 209 x 209	4 x 8 1/4 x 8 1	Mass/ft <sup>2</sup>	22.33 kg 49	9.13 lb		
	Unit/area	22.9 units/m <sup>2</sup>	2.13 units/ft <sup>2</sup>	Mass/ft <sup>2</sup>	23.63 kg 53	1.99 lb		
	Cube ft <sup>2</sup>	56.4	9.4 per row	Mass/ft <sup>2</sup>	28.83 kg 63	3.40 lb		
				Sold sepa	rately			
150 x 300		Dimensions mm	Dimensions				Typical Row	
New		100 x 150 x 300	4 x 5 7/8 x 11	/16				
14000	Unit/area	22.22 units/m <sup>2</sup>	2.06 units/ft <sup>2</sup>					
	Cube ft <sup>2</sup>	69.78	11.63 per rov	Mass/ft <sup>2</sup>	22.33 kg 4	9.13 lb		
aying Patterns 2	209 x 209			Laying Pattern	<b>15</b> 150 x 300			
inear	Checkerboard	Checkerboard	Checkerboard	Parquet	Herringbo	one Heri	ringbone 45°	Linear
TECHNICAL INFOR		lexural Strength Cor	npressive De trength De	g salts freeze-thaw durabi	lity Density	Absorption	Dimen	sion Tolerance*
Boulevard Drain Paver	CSA A231.2	N/A H	50 MPa 45 MPa	25 g/m² after 28 cycles 00 g/m² after 49 cycles	N/A	N/A	Length: Width: Height:	-1.0 to +2.0 mm -1.0 to +2.0 mm ±3.0 mm

Boulevard Drain 209 x 209: Joint spacing is 12 mm (0.47 in.) which allows an initial surface infiltration rate of +/-17 387mm/hr. / Boulevard Drain 150 x 300: Joint spacing is 12 mm (0.47 in.)

Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.