

# Celtik® Wall




	Dimensions mm	Dimensions in.
A	90 x 225 x 175	3 9/16 x 8 7/8 x 6 7/8
B	90 x 225 x 265	3 9/16 x 8 7/8 x 10 7/16
C	90 x 225 x 345	3 9/16 x 8 7/8 x 13 9/16
D	90 x 225 x 435	3 9/16 x 8 7/8 x 17 1/8
Weight/unit (avg.)	14 kg	31 lb
Area/layer (1 to 6)	0.45 m <sup>2</sup>	4.89 ft <sup>2</sup>
<b>Area/cube</b>	<b>3.18 m<sup>2</sup></b>	<b>7 Rows 34.22 ft<sup>2</sup></b>
Qty/cube	A = 28 B = 28 C = 28 D = 28	
Length/rang (1 to 6)	4.88 lin. m	16.00 lin. ft
Length/cube	34.14 lin. m	11.00 lin. ft
Weight/cube	1590 kg	3505 lb


For each unit of 90 mm, 1 alignment pin is included  
 Note: 1/4 layer = 1.22 ft<sup>2</sup>  
 1/8 layer = 0.61 ft<sup>2</sup>

Code	Colour
	<b>Standard</b>
16252364	Range Sheffield Beige & Black
16252362	Range Norvick Grey
Sold by layer	
Production location Trois-Rivières	

### Typical Row



### Laying Pattern



Linear

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Celtik Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

**Applications:** Retaining walls - steps  
**Recommended Capping units:** Celtik Straight Capping unit  
 Additional details: See our landscaping installation guide on our website.