




Leno Capping




Bullnose	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	32.92 lin. m	108 lin. ft
Qty/cube	36 units	3 Rows 36 units
Weight/cube	1387 kg	3057 lb


Code	Colour
Standard	
121000134	Range Amber Beige
10502415	Range Shaded Grey
10502416	Range Scandina Grey
10502414	Rockland Black
Sold by piece Production location St-Eustache	




Straight	Dimensions mm	Dimensions in.
<i>New</i> 	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	32.92 lin. m	108 lin. ft
Qty/cube	36 units	3 Rows 36 units
Weight/cube	1387 kg	3057 lb

Code	Colour
Standard	
121000141	Range Amber Beige
121000139	Range Scandina Grey
121000138	Rockland Black
Sold by piece Production location St-Eustache	



Lafitt	Dimensions mm	Dimensions in.
<i>New</i> 	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	32.92 lin. m	108 lin. ft
Qty/cube	36 units	3 Rows 36 units
Weight/cube	1387 kg	3057 lb

Code	Colour
Standard	
121000137	Range Margaux Beige
121000136	Range Newport Grey
121000135	Rockland Black
Sold by piece Production location St-Eustache	



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Leno Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm