





Melville® 60 Small Rectangle Paver




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	60 x 190 x 380	2 3/8 x 7 1/2 x 15		Prestige	
Weight/unit	10 kg	22 lb	12053044	Range Amber Beige	
Unit/area	13.89 units/m ²	1.29 units/ft ²	12052446	Rockland Black	
Area/layer	0.87 m ²	9.33 ft ²	12052448	Range Scandina Grey	
Area/cube	10.44 m²	12 Rows 111.96 ft²		Standard	
Length/row	4.57 lin. m	15.00 lin. ft	12053043	Range Shaded Grey	
Length/cube	54.86 lin. m	180.00 lin. ft		Sold by layer	
Qty/cube	144 units	144 units		Can be double stacked	
Weight/cube	1465 kg	3225 lb		Production location Montreal, Quebec and Metcalfe	


Laying Patterns



Linear



Herringbone

 1 bag of sand covers approx. 103 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 Slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.