








# Melville® 80 and Melville® 80 DuraFusion Pavers




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	A	80 x 190 x 380		<b>DuraFusion</b>	
	B	80 x 380 x 380	3 1/8 x 15 x 15	10554893 Marbella 	
	C	80 x 380 x 570	3 1/8 x 15 x 22 7/16	10555066 Silverstone 	
Weight/unit (avg.)	27 kg	59 lb	10555067 Hickory 		
Unit/area (avg.)	7.39 units/m <sup>2</sup>	0.69 unit/ft <sup>2</sup>	<b>Prestige</b>		
Area/layer	1.08 m <sup>2</sup>	11.66 ft <sup>2</sup>	10550869 Range Amber Beige		
<b>Area/cube</b>	<b>8.64 m<sup>2</sup></b>	<b>8 Rows</b>	10550447 Range Margaux Beige		
Length/row	3.04 lin. m	9.97 lin. ft	10554764 Range Chambord Grey		
Length/cube	24.32 lin. m	79.79 lin. ft	10550446 Range Scandina Grey		
Weight/cube	1716 kg	3783 lb	10550557 Rockland Black		
			<b>Standard</b>		
			10550868 Range Shaded Grey		
			10550558 Range Newport Grey		

Sold by layer  
Production locations:  
DuraFusion - Metcalfe  
Prestige and Standard - Montreal, Quebec and Metcalfe


## Laying Patterns



Linear



Herringbone

 1 bag of sand covers approx. 116 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville 80 and DuraFusion Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.