



# Melville® 80 and Melville® 80 DuraFusion Pavers




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	A	80 x 190 x 380	3 1/8 x 7 1/2 x 15	<b>DuraFusion</b>	
	B	80 x 380 x 380	3 1/8 x 15 x 15	10554893	Marbella
	C	80 x 380 x 570	3 1/8 x 15 x 22 7/16	10555066	Silverstone
	Weight/unit (avg.)	27 kg	59 lb	10555067	Hickory
	Unit/area (avg.)	7.39 units/m <sup>2</sup>	0.69 unit/ft <sup>2</sup>	<b>Prestige</b>	
	Area/layer	1.08 m <sup>2</sup>	11.66 ft <sup>2</sup>	10550869	Range Amber Beige
	<b>Area/cube</b>	<b>8.64 m<sup>2</sup></b>	<b>8 Rows</b>	10550447	Range Margaux Beige
	Length/row	3.04 lin. m	9.97 lin. ft	10554764	Range Chambord Grey
	Length/cube	24.32 lin. m	79.79 lin. ft	10550446	Range Scandina Grey
	Weight/cube	1716 kg	3783 lb	10550557	Rockland Black
<b>Standard</b>					
10550868				Range Shaded Grey	
10550558				Range Newport Grey	

Sold by layer  
Production locations:  
DuraFusion - Metcalfe  
Prestige and Standard - Montreal, Quebec and Metcalfe

## Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 116 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville 80 and DuraFusion Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.