Mondrian[®] Plus 80 **Small Rectangle Paver**




	eq				
	5				
22:5	-	~~~			
지금 말을 수 있었다.			l Å	\sim	
DEPOTATION NAME	∇	~~~		~	
CONTRACTOR OF A	<u></u>			10 01	
1014年2月1日日	Ψ				
	4			<u> </u>	

	Dimensions mm		
	80 x 165 x 330	3 1/8 x 6 1/2 x 13	
Weight/unit	10 kg	22 lb	
Unit/area	18.52 units/m ²	1.71 units/ft ²	
Area/layer	0.82 m ²	8.79 ft ²	
Area/cube	7.38 m ² 9 Rows	79.11 ft ²	
Length/row	4.95 lin. m	16.25 lin. ft	
Length/cube	59.43 lin. m	195.00 lin. ft	
Qty/cube	135 units	135 units	
Weight/cube	1400 kg	3086 lb	

Code	Colour		
	Prestige		
10550516	Rockland Black		
Sold by laye	r		

Can be double stacked Production location Metcalfe

Typical Row



Laying Patterns

ΤŢΤ		
ТŢТ		
ĽТ	$\frac{1}{1}$	
	<u>, , , , , , , , , , , , , , , , , , , </u>	
	1 1	

Linear

Herringbone

Techniseal 1 bag of sand covers approx. 29 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 80 Small Rectangle Paver	CSA A231.2	N/A	µ 50 MPa ≥ 45 MPa	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).