


Paleo[®] Plus Paver



Pavers




		Dimensions mm	Dimensions in.
A	A	60 x 150 x 130	2 3/8 x 5 7/8 x 5 1/8
	B	60 x 150 x 150	2 3/8 x 5 7/8 x 5 7/8
	C	60 x 150 x 170	2 3/8 x 5 7/8 x 6 11/16
	D	60 x 150 x 188	2 3/8 x 5 7/8 x 7 3/8
B	Unit/area (avg.)	40.40 units/m ²	3.75 units/ft ²
	Area/layer	0.99 m ²	10.66 ft ²
C	Area/cube	11.89 m² 12 Rows	127.89 ft²
	Qty/cube	480 units (A = 96 B = 96 C = 96 D = 192)	
D	Length/row	6.60 lin. m	21.65 lin. ft
	Length/cube	79.20 lin. m	259.85 lin. ft
	Weight/cube	1671 kg	3677 lb

Code	Colour
	Standard
10079015	Range Bourbon Beige
10079016	Range Norvick Grey
Sold by layer	
Can be double stacked	
Production location Quebec	

Typical Row

D	D	D	D	D	D	D	D
A	A	A	A	A	A	A	A
C	C	C	C	C	C	C	C
D	D	D	D	D	D	D	D
B	B	B	B	B	B	B	B

Laying Pattern



Linear

1 bag of sand covers approx. 95 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Paleo Plus Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.