


# Rosebel® Slab



		Dimensions mm	Dimensions in.	
A	A	60 x 389 x 560	2 3/8 x 15 5/16 x 22	
	B	60 x 389 x 756	2 3/8 x 15 5/16 x 29 3/4	
B	Weight/unit (avg.)	24 kg	58 lb	
	Area/unit (avg.)	0.18 m <sup>2</sup>	1.98 ft <sup>2</sup>	
	Area/layer	0.73 m <sup>2</sup>	7.90 ft <sup>2</sup>	
	<b>Area/cube</b>	<b>8.76 m<sup>2</sup></b>	<b>12 Rows</b>	<b>94.80 ft<sup>2</sup></b>
	Qty/cube	48 units	48 units	
	Weight/cube	1159 kg	2550 lb	

Code	Colour	Typical Row
<b>Prestige</b>		
10200631	Range Margaux Beige	
10200632	Range Amboise Beige	
<b>Standard</b>		
10200633	Range Newport Grey	
10200678	Range Norvick Grey	
Sold by layer Can be double stacked Production location Montreal, Quebec and Metcalfe		

Technlseal® 1 bag of sand covers approx. 75 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Rosebel Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm