


# Vendome® 60 and 80 Paver



60 mm  
Not  
vehicular




|                    | Dimensions mm              | Dimensions in.                     |
|--------------------|----------------------------|------------------------------------|
| A                  | 60 x 130 x 197             | 2 3/8 x 5 1/8 x 7 3/4              |
| B                  | 60 x 130 x 262             | 2 3/8 x 5 1/8 x 10 5/16            |
| C                  | 60 x 130 x 327             | 2 3/8 x 5 1/8 x 12 7/8             |
| Weight/unit (avg.) | 4 kg                       | 8,5 lb                             |
| Unit/area (avg.)   | 30.50 units/m <sup>2</sup> | 2.83 units/ft <sup>2</sup>         |
| Area/layer         | 1.05 m <sup>2</sup>        | 11.28 ft <sup>2</sup>              |
| <b>Area/cube</b>   | <b>8.40 m<sup>2</sup></b>  | <b>8 Rows 90.24 ft<sup>2</sup></b> |
| Length/row         | 8.19 lin. m                | 26.87 lin. ft                      |
| Length/cube        | 65.52 lin. m               | 214.96 lin. ft                     |
| Weight/cube        | 1013 kg                    | 2233 lb                            |


| Code     | Colour              |
|----------|---------------------|
|          | <b>Prestige</b>     |
| 10554763 | Rockland Black      |
| 10554761 | Range Margaux Beige |
|          | <b>Standard</b>     |
| 10554762 | Range Newport Grey  |

Sold by layer  
Production location Bolton

Typical Row



80 mm




|                    | Dimensions mm              | Dimensions in.                     |
|--------------------|----------------------------|------------------------------------|
| A                  | 80 x 130 x 197             | 3 1/8 x 5 1/8 x 7 3/4              |
| B                  | 80 x 130 x 262             | 3 1/8 x 5 1/8 x 10 5/16            |
| C                  | 80 x 130 x 327             | 3 1/8 x 5 1/8 x 12 7/8             |
| Weight/unit (avg.) | 6 kg                       | 12 lb                              |
| Unit/area (avg.)   | 30.50 units/m <sup>2</sup> | 2.83 units/ft <sup>2</sup>         |
| Area/layer         | 1.05 m <sup>2</sup>        | 11.28 ft <sup>2</sup>              |
| <b>Area/cube</b>   | <b>8.40 m<sup>2</sup></b>  | <b>8 Rows 90.24 ft<sup>2</sup></b> |
| Qty/cube           | A = 88    B = 96    C = 72 |                                    |
| Length/row         | 7.86 lin. m                | 25.80 lin. ft                      |
| Length/cube        | 62.90 lin. m               | 206.40 lin. ft                     |
| Weight/cube        | 1468 kg                    | 3236 lb                            |


| Code     | Colour              |
|----------|---------------------|
|          | <b>Prestige</b>     |
| 10550002 | Rockland Black      |
| 10559011 | Range Margaux Beige |
|          | <b>Standard</b>     |
| 10559010 | Range Newport Grey  |

Sold by layer  
Production location Montreal


Typical Row



## Laying Patterns



Linear



Modular

Techniseal 1 bag of sand covers approx. : Vendome 60 - 44 ft<sup>2</sup> / Vendome 80 - 33 ft<sup>2</sup>

## TECHNICAL INFORMATION

| Product       | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability  | Density | Absorption | Dimension Tolerance*   |
|---------------|------------|-------------------|----------------------|--|---------|------------|--|
| Vendome Paver | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).