

# Vendome® 60 and 80 Paver




60 mm		Dimensions mm	Dimensions in.	
Not vehicular	A	60 x 130 x 197	2 3/8 x 5 1/8 x 7 3/4	
	B	60 x 130 x 262	2 3/8 x 5 1/8 x 10 5/16	
	C	60 x 130 x 327	2 3/8 x 5 1/8 x 12 7/8	
A B C	Weight/unit (avg.)	4 kg	8,5 lb	
	Unit/area (avg.)	30.50 units/m <sup>2</sup>	2.83 units/ft <sup>2</sup>	
	Area/layer	1.05 m <sup>2</sup>	11.28 ft <sup>2</sup>	
	<b>Area/cube</b>	<b>8.40 m<sup>2</sup></b>	<b>8 Rows</b>	<b>90.24 ft<sup>2</sup></b>
	Length/row	8.19 lin. m	26.87 lin. ft	
	Length/cube	65.52 lin. m	214.96 lin. ft	
	Weight/cube	1013 kg	2233 lb	

80 mm		Dimensions mm	Dimensions in.	
A	A	80 x 130 x 197	3 1/8 x 5 1/8 x 7 3/4	
	B	80 x 130 x 262	3 1/8 x 5 1/8 x 10 5/16	
	C	80 x 130 x 327	3 1/8 x 5 1/8 x 12 7/8	
A B C	Weight/unit (avg.)	6 kg	12 lb	
	Unit/area (avg.)	30.50 units/m <sup>2</sup>	2.83 units/ft <sup>2</sup>	
	Area/layer	1.05 m <sup>2</sup>	11.28 ft <sup>2</sup>	
	<b>Area/cube</b>	<b>8.40 m<sup>2</sup></b>	<b>8 Rows</b>	<b>90.24 ft<sup>2</sup></b>
	Qty/cube	A = 88    B = 96    C = 72		
	Length/row	7.86 lin. m	25.80 lin. ft	
	Length/cube	62.90 lin. m	206.40 lin. ft	
Weight/cube	1468 kg	3236 lb		


Code	Colour
	<b>Prestige</b>
10554763	Rockland Black
10554761	Range Margaux Beige
	<b>Standard</b>
10554762	Range Newport Grey

Sold by layer  
Production location Bolton




Code	Colour
	<b>Prestige</b>
10550002	Rockland Black
10559011	Range Margaux Beige
	<b>Standard</b>
10559010	Range Newport Grey


Sold by layer  
Production location Montreal



## Laying Patterns



Linear



Modular

Techniseal 1 bag of sand covers approx. : Vendome 60 - 44 ft<sup>2</sup> / Vendome 80 - 33 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vendome Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).