


Vertex Paver *New*




Light Commercial

		Dimensions mm	Dimensions in.	Colour	Typical Row
A	A and B	100 x 150 and 300 x 600	4 x 5 7/8 and 11 13/16 x 23 5/8	Standard	
	Area/unit (avg.)	0.135 m ²	1.45 ft ²	White - Smooth	
B				Cinder Grey - Smooth	
				Charcoal - Smooth	
			Light Charcoal - Smooth		
			Black ETX - Smooth		
			Light Grey - Smooth		
			Beige Grey - Smooth		
			Beige - Smooth		
			Production location Montreal		


Laying Patterns



Diagonal 100 x 450
with Boulevard 300 pavers
100 x 450




False Curves
with Boulevard 300 pavers
150 x 150
with Boulevard 300 pavers
150 x 300



Insertions 300 x 600
with Boulevard 300 pavers
300 x 600




Garden 600 x 600
with Boulevard 300 pavers
600 x 600




Verde Lines
with Boulevard Verde pavers



Rows 150 x 450
with Boulevard 300 pavers
150 x 450



Side-by-side 150 and 300
with Boulevard 300 pavers
150 x 150
with Boulevard 300 pavers
150 x 300



Side-by-side 150 x 300
with Boulevard 300 pavers
150 x 300

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vertex Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.