

# Grande Wall



## 375 Standard




	Dimensions mm	Dimensions in.
	200 x 375 x 1000	7 7/8 x 14 3/4 x 39 3/8
Weight/unit	161 kg	360 lb
Area/layer	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
Area/cube	1.80 m <sup>2</sup>	19.56 ft <sup>2</sup>
Length/cube	9.00 lin. m	29.60 lin. ft
<b>Qty/cube</b>	<b>9 units</b>	<b>9 units</b>
Weight/cube	1500 kg	3300 lb

## Code Colour

**Standard**

16201336 Grey  
 Call for custom colour information  
 Sold in full cubes only  
 Production location Cambridge

## Typical Row



## 750 Standard




	Dimensions mm	Dimensions in.
	200 x 750 x 1000	7 7/8 x 29 1/2 x 39 3/8
Weight/unit	328 kg	726 lb
Area/layer	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
Area/cube	0.80 m <sup>2</sup>	8.70 ft <sup>2</sup>
Length/cube	4.00 lin. m	13.10 lin. ft
<b>Qty/cube</b>	<b>4 units</b>	<b>4 units</b>
Weight/cube	1350 kg	2970 lb

## Code Colour

**Standard**

16209043 Grey  
 Call for custom colour information  
 Sold in full cubes only  
 Production location Cambridge

## Typical Row



## 1125 Standard




	Dimensions mm	Dimensions in.
	200 x 1125 x 1000	7 7/8 x 44 5/16 x 39 3/8
Weight/unit	483 kg	1065 lb
Area/layer	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
Area/cube	0.60 m <sup>2</sup>	6.45 ft <sup>2</sup>
Length/cube	3.00 lin. m	9.90 lin. ft
<b>Qty/cube</b>	<b>3 units</b>	<b>3 units</b>
Weight/cube	1450 kg	3190 lb

## Code Colour

**Standard**

16209044 Grey  
 Call for custom colour information  
 Sold in full cubes only  
 Production location Cambridge

## Typical Row



## Clamps

## Code

70970830 SM Clamp  
 70970833 LG Clamp

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

# Grande Wall

## Corner Unit




	Dimensions mm	Dimensions in.
	200 x 500 x 1000	7 7/8 x 19 11/16 x 39 3/8
Weight/unit	213 kg	469 lb
Unit/area	3.33 units/m <sup>2</sup>	0.31 unit/ft <sup>2</sup>
<b>Qty/cube</b>	<b>6 units*</b>	<b>6 units*</b>
Weight/cube	1278 kg	2811 lb

\* 6 units equal: 3 right units, 3 left units

Code	Colour
	<b>Standard</b>

16209045 Grey  
Call for custom colour information  
Sold in full cubes only  
Production location Cambridge

### Typical Row



## Step 175




	Dimensions mm	Dimensions in.
	175 x 438 x 1000	6 7/8 x 17 1/4 x 39 3/8
Weight/unit	175 kg	386 lb
Length/cube	1.20 lin. m	19.68 lin. ft
<b>Qty/cube</b>	<b>6 units*</b>	<b>6 units*</b>
Weight/cube	1070 kg	2358 lb

\* 6 units equal: 3 right units, 3 left units

Code	Colour
	<b>Standard</b>

16202415 Grey  
16202416 Desert Grey  
16202417 Granite  
16202418 Onyx Brown  
Sold in full cubes only  
Production location Cambridge

### Typical Row



## Capping 438




	Dimensions mm	Dimensions in.
	200 x 438 x 1000	7 7/8 x 17 1/4 x 39 3/8
Weight/unit	194 kg	427 lb
Unit/area	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
<b>Qty/cube</b>	<b>6 units</b>	<b>6 units</b>
Weight/cube	1162 kg	2561 lb

Code	Colour
	<b>Standard</b>

16200460 Grey  
16201338 Desert Grey  
16201339 Granite  
16201340 Onyx Brown  
Sold in full cubes only  
Production location Cambridge

### Typical Row



## Grande Wall - Custom Splitting




Custom splitting is available for corners at custom angles or for coping units at the end of a wall. **Splitting premium is in addition to the price of the unit being split.**

Sold in full cubes only  
Production location - Cambridge

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

# Grande Wedge<sup>®</sup> Standard Wall and Capping




## Standard Wall




	Dimensions mm	Dimensions in.
	200 x 312.5 x 380 - 250	7 7/8 x 12 5/16 x 14 15/16 - 9 27/32
Weight/unit	38 kg	83 lb
Unit/area	13.16 units/m <sup>2</sup>	1.22 units/ft <sup>2</sup>
Area/cube	2.74 m <sup>2</sup>	29.50 ft <sup>2</sup>
Length/cube	13.68 lin m	44.90 lin. ft
<b>Qty/cube</b>	<b>36 units</b>	<b>36 units</b>
Weight/cube	1353 kg	2978 lb

Code	Colour
16200459	Grey
<b>Standard</b>	
Call for custom colour information	
Sold in full cubes	
Production location Cambridge	

## Typical Row



## Laying Pattern



Linear


## Capping



	Dimensions mm	Dimensions in.
	100 x 312.5 x 380 - 250	3 15/16 x 12 8/32 x 14 15/16 - 9 27/32
Weight/unit	21 kg	47 lb
Length/cube	23.94 lin. m	78.50 lin. ft
<b>Qty/cube</b>	<b>63 units</b>	<b>63 units</b>
Weight/cube	1329 kg	2978 lb

Code	Colour
16200458	Grey
<b>Standard</b>	
Call for custom colour information	
Sold in full cubes	
Production location Cambridge	

## Typical Row



## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Grande Wedge Standard Wall and Capping</b>	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

**Recommended Capping:** Grande Wedge Capping Unit

**Applications:** Retaining Walls

**Features:** Wedge Units create a 1000 mm (3'3") outside radius without cutting - 4 Wedge units are required for a rounded 90° corner, 16 pcs for a full circle - Two thirds of all Wedge units in a bundle come double rock-faced for inside and outside curves. Engineering required for walls greater than 1.0 m (3.3 ft)