



# Kensington Smooth Paver




Rectangle	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	80 x 209 x 279	3 1/8 x 8 1/4 x 11	10506699	Sierra Black	
Weight/unit	10.29 kg	22.70 lb	Sold in full cubes only		
Units/area	-	1.55 units/ft <sup>2</sup>	Production location Cambridge		
Area/section	-	23.17 ft <sup>2</sup>			
Area/cube	-	91.14 ft <sup>2</sup>			
Length/section	-	25 lin. ft			
Length/cube	-	100 lin. ft			
Qty	144 units/cube	36 units/section			
Weight	1486 kg	3270 lb			

Mixed Bundle	Dimensions mm	Dimensions in.	Code	Colour	Typical Row	
	C	80 x 279 x 419	3 1/8 x 11 x 16 1/2	10506622	Ash Grey Blend	
	Weight/unit	21.36 kg	47.10 lb	10506693	Canyon Grey Blend	
	Units/area	-	0.78 unit/ft <sup>2</sup>	10506694	Desert Grey Blend	
	Qty/cube	36 units	36 units	10506692	Granite Blend	
	B	80 x 279 x 279	3 1/8 x 11 x 11	Sold in full cubes only		
Weight/unit	14.33 kg	31.60 lb	Production location Woodstock			
Units/area	-	1.17 units/ft <sup>2</sup>				
Qty/cube	36 units	36 units				
A	80 x 139 x 279	3 1/8 x 5 1/2 x 11				
Weight/unit	7.07 kg	15.60 lb				
Units/area	-	2.32 units/ft <sup>2</sup>				
Qty/cube	36 units	36 units				
Area/cube	-	91.14 ft <sup>2</sup>				
Weight/cube	1507 kg	3316 lb				


## Laying Pattern




Pattern 1:  
3 Stone Random



Pattern 2:  
3 Stone Running Bond



Pattern 3: Herringbone  
100% Rectangle



Pattern 4: Running Bond  
100% Rectangle

1 bag of sand covers approx. 37 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Kensington Smooth Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient (mixed bundle): 247 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.