


# Vertex Paver *New*




Light Commercial

		Dimensions mm	Dimensions in.	Colour	Typical Row
A	A and B	100 x 150 and 300 x 600	4 x 5 7/8 and 11 13/16 x 23 5/8	<b>Standard</b>	
B	Area/unit (avg.)	0.135 m <sup>2</sup>	1.45 ft <sup>2</sup>	White - Smooth	
				Cinder Grey - Smooth	
				Charcoal - Smooth	
				Light Charcoal - Smooth	
				Black ETX - Smooth	
				Light Grey - Smooth	
				Beige Grey - Smooth	
				Beige - Smooth	
				Production location Montreal	

## Laying Patterns



Diagonal 100 x 450  
with Boulevard 300 pavers  
100 x 450




False Curves  
with Boulevard 300 pavers  
150 x 150  
with Boulevard 300 pavers  
150 x 300



Insertions 300 x 600  
with Boulevard 300 pavers  
300 x 600




Garden 600 x 600  
with Boulevard 300 pavers  
600 x 600




Verde Lines  
with Boulevard Verde pavers



Rows 150 x 450  
with Boulevard 300 pavers  
150 x 450



Side-by-side 150 and 300  
with Boulevard 300 pavers  
150 x 150  
with Boulevard 300 pavers  
150 x 300



Side-by-side 150 x 300  
with Boulevard 300 pavers  
150 x 300

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vertex Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.