


Agora Paver



Light Commercial

80 mm




	Dimensions mm	Dimensions in.
A	80 x 167 x 300	3 1/8 x 6 9/16 x 11
B	80 x 200 x 300	3 1/8 x 7 7/8 x 11
C	80 x 233 x 300	3 1/8 x 9 3/16 x 11
Weight/unit (avg.)	11 kg	24 lb
Unit/area (avg.)	13.27 units/m ²	1.51 units/ft ²
Area/layer	0.86 m ²	9.26 ft ²
Area/cube	6.88 m²	8 Rows 74.08 ft²
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	33.60 lin. m	110.24 lin. ft
Weight/cube	1265 kg	2789 lb

Colour

Standard
Rockland Black
Range Amber Beige
Range Shaded Grey
Range Scandina Grey

A, B, C are sold together

Typical Row



Large Rectangle 80 mm




	Dimensions mm	Dimensions in.
	80 x 233 x 300	3 1/8 x 9 3/16 x 11
Weight/unit (avg.)	13 kg	28 lb
Unit/area (avg.)	14.28 units/m ²	1.33 units/ft ²
Area/layer	0.98 m ²	10.55 ft ²
Area/cube	7.84 m²	8 Rows 84.40 ft²
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	33.60 lin. m	110.24 lin. ft
Qty/cube	112 units	112 units
Weight/cube	1440 kg	3175 lb


Colour

Standard
Rockland Black
Range Amber Beige
Range Shaded Grey
Range Scandina Grey

Typical Row



100 mm




	Dimensions mm	Dimensions in.
A	100 x 167 x 300	4 x 6 9/16 x 11
B	100 x 200 x 300	4 x 7 7/8 x 11
C	100 x 233 x 300	4 x 9 3/16 x 11
Weight/unit (avg.)	13 kg	29 lb
Unit/area (avg.)	13.27 units/m ²	1.51 units/ft ²
Area/layer	0.86 m ²	9.26 ft ²
Area/cube	8.60 m²	10 Rows 92.60 ft²
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	42 lin. m	137.80 lin. ft
Weight/cube	1898 kg	4184 lb

Colour

Standard
Rockland Black
Range Amber Beige
Range Shaded Grey
Range Scandina Grey

Typical Row



Agora Paver - cont'd


Large Rectangle
100 mm




	Dimensions mm	Dimensions in.
	100 x 233 x 300	4 x 9 3/16 x 11
Weight/unit (avg.)	15.6 kg	33.1 lb
Unit/area (avg.)	14.28 units/m ²	1.33 units/ft ²
Area/layer	0.98 m ²	10.55 ft ²
Area/cube	9.80 m²	10 Rows
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	42 lin. m	137.80 lin. ft
Qty/cube	140 units	140 units
Weight/cube	2184 kg	4704 lb

Colour
Standard
Rockland Black
Range Amber Beige
Range Shaded Grey
Range Scandina Grey

Typical Row



Laying Pattern



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Agora Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.