


Celtik® Straight Capping



| | Dimensions mm | Dimensions in. |
|-----------------|-------------------|----------------------|
| | 90 x 305 x 400 | 3 9/16 x 12 x 15 3/4 |
| Weight/unit | 27 kg | 59 lb |
| Units/length | 2.50 units/lin. m | 0.76 unit/lin. ft |
| Length/row | 3.60 lin. m | 11.84 lin. ft |
| Length/cube | 28.80 lin. m | 94.74 lin. ft |
| Qty/cube | 72 units | 8 Rows |
| Weight/cube | 1921 kg | 4225 lb |

| Code | Colour |
|------------------------------------|-------------------------------|
| | Standard |
| 16259032 | Range Norvick Grey |
| 16259035 | Range Sheffield Beige & Black |
| Sold by piece | |
| Production location Trois-Rivières | |

Typical Row



Capping and Steps

TECHNICAL INFORMATION

| Product | Standard | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|--------------------------------|-------------|-------------------|----------------------|---------------------------------------|------------------------|------------|--|
| Celtik Straight Capping | ASTM C 1372 | N/A | 20.7 MPa | N/A | 2000 kg/m ³ | 10.4% | Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm |

Additional details specific to this product are available by consulting our landscaping installation guide on our website.