

# Celtik® Wall



textured



|                      | Dimensions mm               | Dimensions in.                     |
|----------------------|-----------------------------|------------------------------------|
| A                    | 90 x 225 x 175              | 3 9/16 x 8 7/8 x 6 7/8             |
| B                    | 90 x 225 x 265              | 3 9/16 x 8 7/8 x 10 7/16           |
| C                    | 90 x 225 x 345              | 3 9/16 x 8 7/8 x 13 9/16           |
| D                    | 90 x 225 x 435              | 3 9/16 x 8 7/8 x 17 1/8            |
| Weight/unit (avg.)   | 14 kg                       | 31 lb                              |
| Area/layer (1 to 6)  | 0.45 m <sup>2</sup>         | 4.89 ft <sup>2</sup>               |
| <b>Area/cube</b>     | <b>3.18 m<sup>2</sup></b>   | <b>7 Rows 34.22 ft<sup>2</sup></b> |
| Qty/cube             | A = 28 B = 28 C = 28 D = 28 |                                    |
| Length/rang (1 to 6) | 4.88 lin. m                 | 16.00 lin. ft                      |
| Length/cube          | 34.14 lin. m                | 11.00 lin. ft                      |
| Weight/cube          | 1590 kg                     | 3505 lb                            |


For each unit of 90 mm, 1 alignment pin is included

Note: 1/4 layer = 1.22 ft<sup>2</sup>


1/8 layer = 0.61 ft<sup>2</sup>

| Code                               | Colour                        |
|------------------------------------|-------------------------------|
|                                    | <b>Standard</b>               |
| 16252364                           | Range Sheffield Beige & Black |
| 16252362                           | Range Norvick Grey            |
| Sold by layer                      |                               |
| Production location Trois-Rivières |                               |

## Typical Row



## Laying Pattern



Linear

## TECHNICAL INFORMATION

| Product     | Standard    | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density                | Absorption | Dimension Tolerance*                                 |
|-------------|-------------|-------------------|----------------------|---------------------------------------|------------------------|------------|--|
| Celtik Wall | ASTM C 1372 | N/A               | 20.7 MPa             | N/A                                   | 2000 kg/m <sup>3</sup> | 10.4%      | Length: ±3.2 mm<br>Width: ±3.2 mm<br>Height: ±3.2 mm |

**Applications:** Retaining walls - steps

**Recommended Capping units:** Celtik Straight Capping unit

Additional details: See our landscaping installation guide on our website.