


# Melville® 60 and Melville® 60 DuraFusion Slabs




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row	
	A	60 x 190 x 380	2 3/8 x 7 1/2 x 15			
	B	60 x 380 x 380	2 3/8 x 15 x 15			
	C	60 x 380 x 570	2 3/8 x 15 x 22 7/16			
	Weight/unit (avg.)	19 kg	42 lb			
	Unit/area (avg.)	0.14 unit/m <sup>2</sup>	1.46 units/ft <sup>2</sup>			
	Area/layer	1.08 m <sup>2</sup>	11.66 ft <sup>2</sup>			
	<b>Area/cube</b>	<b>10.80 m<sup>2</sup></b>	<b>10 Rows</b>	<b>116.60 ft<sup>2</sup></b>		
	Qty/cube	80 units	80 units			
	Weight/cube	1538 kg	3391 lb			
				<b>DuraFusion</b>		
			12051953	Marbella		
			12051954	Silverstone		
			12051955	Hickory		
			<b>Prestige</b>			
			12053046	Range Amber Beige		
			12052734	Range Margaux Beige		
			12052104	Range Chambord Grey		
			12052365	Range Scandina Grey		
			12052732	Rockland Black		
			<b>Standard</b>			
			12053045	Range Shaded Grey		
			12052733	Range Newport Grey		

Sold by layer  
 Can be double stacked  
 Production locations:  
 DuraFusion - Metcalfe  
 Prestige and Standard - Montreal, Quebec and Metcalfe

### Laying Patterns



Modular



Linear

1 bag of sand covers approx. 155 ft<sup>2</sup>

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville 60 Slab</b>	CSA A231.1	±4.5 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.