



# Melville® 60 Small Rectangle Paver




	Dimensions mm	Dimensions in.
	60 x 190 x 380	2 3/8 x 7 1/2 x 15
Weight/unit	10 kg	22 lb
Unit/area	13.89 units/m <sup>2</sup>	1.29 units/ft <sup>2</sup>
Area/layer	0.87 m <sup>2</sup>	9.33 ft <sup>2</sup>
<b>Area/cube</b>	<b>10.44 m<sup>2</sup> 12 Rows</b>	<b>111.96 ft<sup>2</sup></b>
Length/row	4.57 lin. m	15.00 lin. ft
Length/cube	54.86 lin. m	180.00 lin. ft
Qty/cube	144 units	144 units
Weight/cube	1465 kg	3225 lb


Code	Colour
<b>Prestige</b>	
12053044	Range Amber Beige
12052446	Rockland Black
12052448	Range Scandina Grey
<b>Standard</b>	
12053043	Range Shaded Grey
Sold by layer	
Can be double stacked	
Production location Montreal, Quebec and Metcalfe	



## Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 103 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville 60 Small Rectangle Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 Slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.