


Melville® 80 and Melville® 80 DuraFusion Pavers




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	A	80 x 190 x 380	3 1/8 x 7 1/2 x 15		
	B	80 x 380 x 380	3 1/8 x 15 x 15		
	C	80 x 380 x 570	3 1/8 x 15 x 22 7/16		
	Weight/unit (avg.)	27 kg	59 lb		
	Unit/area (avg.)	7.39 units/m ²	0.69 unit/ft ²		
	Area/layer	1.08 m ²	11.66 ft ²		
	Area/cube	8.64 m²	8 Rows	93.28 ft²	
	Length/row	3.04 lin. m	9.97 lin. ft		
	Length/cube	24.32 lin. m	79.79 lin. ft		
	Weight/cube	1716 kg	3783 lb		


Code	Colour	
DuraFusion		
10554893	Marbella	
10555066	Silverstone	
10555067	Hickory	
Prestige		
10550869	Range Amber Beige	
10550447	Range Margaux Beige	
10554764	Range Chambord Grey	
10550446	Range Scandina Grey	
10550557	Rockland Black	
Standard		
10550868	Range Shaded Grey	
10550558	Range Newport Grey	

Sold by layer
 Production locations:
 DuraFusion - Metcalfe
 Prestige and Standard - Montreal, Quebec and Metcalfe

Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 116 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 and DuraFusion Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
 Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.