Metrik™ Slab















s in.	Dimensions mm										
4 x 11	2 3/8	60 x 70 x 280		30		30		60 x 70 x 280		60 x 70 x 2	
	5.96 l	2.7 kg		2.7 kg		Weight/unit					
	$0.02 \ m^2$ $0.21 \ ft^2$		0.02 m ²		0.02 m ²		Area/unit				
	9.95 f			0.92 m ²	Area/layer						
	119.4	12 Rows		11.09 m ²	Area/cube						
	576 u			576 units	Qty/cube						
	3434	1558 kg		t/cube 1558 kg		Weight/cube					


Code	Colour	Typical Row		
	Prestige			
10502884	Blizzard			
10502882	Rockland Black			
127000940	Range Scandina Grey - //			
Sold by layer Can be doub Production lo				


 1	

Laying Patterns









Checkerboard

Offset 1/2

Offset 1/3

Herringbone

○ Techniseal 1 bag of sand covers approx. 55 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Metrik Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

 $^{^\}star$ Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

 $Cover snow \, removal \, tools \, with \, Teflon \, or \, neoprene \, protectors \, to \, minimize \, the \, risk \, of \, damage \, from \, scratches. \, Laying \, patterns \, are \, for \, design \, purposes \, only. \, Permacon \, shall \, not \, be \, responsible \, for \, excess \, or \, shortage \, of \, material.$

