



# Mondrian® Plus 60 Slab




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
A	A	60 x 165 x 330	2 3/8 x 6 1/2 x 13	12052893	Range Margaux Beige	
	B	60 x 330 x 330	2 3/8 x 13 x 13			
	C	60 x 330 x 495	2 3/8 x 13 x 19 1/2			
B	Weight/unit (avg.)	14 kg	30 lb	12052894	Range Amboise Beige	
	Area/unit	0.11 m <sup>2</sup>	1.17 ft <sup>2</sup>	12052566	Range Scandinia Grey	
C	Area/layer	0.98 m <sup>2</sup>	10.55 ft <sup>2</sup>	<b>Standard</b>		
	<b>Area/cube</b>	<b>11.76 m<sup>2</sup></b>	<b>12 Rows</b>	<b>12052891</b>	Range Norvick Grey	
	Qty/cube	A = 48	B = 48	C = 24	12052892	Range Newport Grey
	Weight/cube	1666 kg	3667 lb	Sold by layer Can be double stacked Production location Montreal, Quebec and St-Eustache		


## Laying Patterns



Linear  
100% Mix A, B, C



Modular  
100% Mix A, B, C



Modular  
100% Mix A, B, C

1 bag of sand covers approx. 57 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Mondrian Plus 60 Slab</b>	CSA A231.1	±4.5 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.