Mondrian® Plus 60 Small Rectangle Paver

















	Dimensions mm	Dimensions in.		
	60 x 330 x 165	2 3/8 x 13 x 6 1/2		
Weight/unit	7.7 kg	17 lb		
Unit/area	18.52 units/m ²	1.71 units/ft²		
Area/layer	0.82 m ²	8.79 ft ²		
Area/cube	9.84 m ² 12 Rows	105.48 ft ²		
Length/row	4.95 lin. m	16.25 lin. ft		
Length/cube	59.43 lin. m	195.00 lin. ft		
Qty/cube	180 units	180 units		
Weight/cube	1389 kg	3062 lb		

Code	Colour	Typical Row
	Prestige	
12052557	Rockland Black	
Sold by layer Production location Metcalfe		

Laying Patterns





Linear

Herringbone

☼ Techniseal 1 bag of sand covers approx. 38 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 60 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.

The Mondrian Plus 60 Slab is compatible with the Mondrian Plus 60 small rectangle paver for non-vehicular application only.