


# Paleo-Tec Paver



Heavy Commercial




|                  | Dimensions mm              | Dimensions in.              |
|------------------|----------------------------|-----------------------------|
|                  | 100 x 140 x 220            | 4 x 5 1/2 x 8 5/8           |
| Weight/unit      | 6.80 kg                    | 15.00 lb                    |
| Unit/area        | 32.50 units/m <sup>2</sup> | 3.00 units/ft <sup>2</sup>  |
| Area/layer       | 0.99 m <sup>2</sup>        | 10.62 ft <sup>2</sup>       |
| <b>Area/cube</b> | <b>5.92 m<sup>2</sup></b>  | <b>63.72 ft<sup>2</sup></b> |
| Length/row       | 7.01 lin. m                | 23.00 lin. ft               |
| Length/cube      | 42.06 lin. m               | 138.00 lin. ft              |
| Weight/cube      | 1306 kg                    | 2880 lb                     |


| Code     | Colour               |
|----------|----------------------|
|          | <b>Standard</b>      |
| 10102026 | Light Grey           |
| 10109059 | Range Brownstone Red |
| 10109067 | Range Norvick Grey   |
| 10103056 | Rockland Black       |

Production location Woodstock

Typical Row



## Laying Pattern



Linear

## TECHNICAL INFORMATION

| Product                | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability  | Density | Absorption | Dimension Tolerance*   |
|------------------------|------------|-------------------|----------------------|--|---------|------------|--|
| <b>Paleo-Tec Paver</b> | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.