

# Universal Slope Block




	Dimensions mm	Dimensions in.
	135 x 280 x 215	5 5/16 x 11 x 8 1/2
Weight/unit	19 kg	40 lb
Unit/area	34.46 units/m <sup>2</sup>	3.20 units/ft <sup>2</sup>
Area/cube	2.32 m <sup>2</sup>	25.00 ft <sup>2</sup>
<b>Qty/cube</b>	<b>80 units</b>	<b>4 Rows</b>
Weight/cube	1490 kg	3278 lb

Code	Colour
	<b>Standard</b>
16259199	Grey

Sold by piece  
Production location Quebec

### Typical Row



Packaged vertically



## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Universal Slope Block</b>	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

**Applications:** Retaining walls  
Additional details: See our landscaping installation guide on our website.


# Split Face Universal Slope Block



	Dimensions mm		Dimensions in.		Code	Colour	Typical Row
	Standard		Standard				
Weight/unit	20 kg	43 lb			16259167	Grey	
Unit/area	34.40 units/m <sup>2</sup>	3.20 units/ft <sup>2</sup>			Sold in double unit		
Area/cube	2.32 m <sup>2</sup>	25.00 ft <sup>2</sup>			Splitting required		
Qty/cube	<b>80 units</b>	<b>4 Rows</b>	<b>80 units</b>			Production location Quebec	
Weight/cube	1590 kg	3498 lb					

Packaged vertically

## Laying Pattern



Linear

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Split Face Universal Slope Block</b>	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

**Applications:** Retaining walls  
Additional details specific to this product are available by consulting our landscaping installation guide on our website.