


# Agora Paver



Light Commercial

## 80 mm




	Dimensions mm	Dimensions in.
A	80 x 167 x 300	3 1/8 x 6 9/16 x 11
B	80 x 200 x 300	3 1/8 x 7 7/8 x 11
C	80 x 233 x 300	3 1/8 x 9 3/16 x 11
Weight/unit (avg.)	11 kg	24 lb
Unit/area (avg.)	13.27 units/m <sup>2</sup>	1.51 units/ft <sup>2</sup>
Area/layer	0.86 m <sup>2</sup>	9.26 ft <sup>2</sup>
<b>Area/cube</b>	<b>6.88 m<sup>2</sup></b>	<b>8 Rows 74.08 ft<sup>2</sup></b>
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	33.60 lin. m	110.24 lin. ft
Weight/cube	1265 kg	2789 lb

## Colour

### Standard

Rockland Black  
Range Amber Beige  
Range Shaded Grey  
Range Scandina Grey  
A, B, C are sold together

## Typical Row



## Large Rectangle 80 mm




	Dimensions mm	Dimensions in.
	80 x 233 x 300	3 1/8 x 9 3/16 x 11
Weight/unit (avg.)	13 kg	28 lb
Unit/area (avg.)	14.28 units/m <sup>2</sup>	1.33 units/ft <sup>2</sup>
Area/layer	0.98 m <sup>2</sup>	10.55 ft <sup>2</sup>
<b>Area/cube</b>	<b>7.84 m<sup>2</sup></b>	<b>8 Rows 84.40 ft<sup>2</sup></b>
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	33.60 lin. m	110.24 lin. ft
Qty/cube	112 units	112 units
Weight/cube	1440 kg	3175 lb

## Colour


### Standard

Rockland Black  
Range Amber Beige  
Range Shaded Grey  
Range Scandina Grey

## Typical Row



## 100 mm




	Dimensions mm	Dimensions in.
A	100 x 167 x 300	4 x 6 9/16 x 11
B	100 x 200 x 300	4 x 7 7/8 x 11
C	100 x 233 x 300	4 x 9 3/16 x 11
Weight/unit (avg.)	13 kg	29 lb
Unit/area (avg.)	13.27 units/m <sup>2</sup>	1.51 units/ft <sup>2</sup>
Area/layer	0.86 m <sup>2</sup>	9.26 ft <sup>2</sup>
<b>Area/cube</b>	<b>8.60 m<sup>2</sup></b>	<b>10 Rows 92.60 ft<sup>2</sup></b>
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	42 lin. m	137.80 lin. ft
Weight/cube	1898 kg	4184 lb

## Colour

### Standard

Rockland Black  
Range Amber Beige  
Range Shaded Grey  
Range Scandina Grey  
A, B, C are sold together

## Typical Row



# Agora Paver - cont'd


Large Rectangle  
100 mm




	Dimensions mm	Dimensions in.
	100 x 233 x 300	4 x 9 3/16 x 11
Weight/unit (avg.)	15.6 kg	33.1 lb
Unit/area (avg.)	14.28 units/m <sup>2</sup>	1.33 units/ft <sup>2</sup>
Area/layer	0.98 m <sup>2</sup>	10.55 ft <sup>2</sup>
<b>Area/cube</b>	<b>9.80 m<sup>2</sup></b>	<b>10 Rows</b>
Length/row	4.20 lin. m	13.78 lin. ft
Length/cube	42 lin. m	137.80 lin. ft
Qty/cube	140 units	140 units
Weight/cube	2184 kg	4704 lb

Colour
<b>Standard</b>
Rockland Black
Range Amber Beige
Range Shaded Grey
Range Scandina Grey

Typical Row



## Laying Pattern



Linear

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Agora Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.