## Mega Lafitt® Plus Step









|             | Dimensi          | ons mm | Dimensions in. |  |
|-------------|------------------|--------|----------------|--|
|             | 180 x 406 x 1219 |        | 7 x 16 x 48    |  |
| Weight/unit | 200 kg           |        | 441 lb         |  |
| Length/cube | 7.31 lin. m      |        | 24 lin. ft     |  |
| Qty/cube    | 6 units          | 3 Rows | 6 units        |  |
| Weight/cube | 1143 kg          |        | 2740 lb        |  |
|             |                  |        |                |  |

| Code     | Colour              |  |  |
|----------|---------------------|--|--|
|          | Standard            |  |  |
| 16204026 | Range Margaux Beige |  |  |
| 16203211 | Range Newport Grey  |  |  |
| 16204028 | Rockland Black      |  |  |

| Iy | pical Row |  |
|----|-----------|--|
|    |           |  |
|    |           |  |
|    |           |  |
|    |           |  |
|    |           |  |
|    |           |  |

## TECHNICAL INFORMATION

| Product                  | Standard | Flexural Strength | Compressive<br>Strength | De-icing salts freeze-thaw durability | Density                | Absorption | Dimension Tolerance*   |
|--------------------------|----------|-------------------|-------------------------|---------------------------------------|------------------------|------------|--|
| Mega Lafitt Plus<br>Step | N/A      | N/A               | 35 MPa                  | 500 g/m²                              | 2250 kg/m <sup>3</sup> | 5%         | Length: ±2.0 mm<br>Width: ±2.0 mm<br>Height: -2.0 to +1.0 mm |

Given the weight of this step unit, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation), or specialized handling equipment such as a clamp adapted for this type of product. The Grande wall unit clamp can also be used. Additional details: See our landscaping installation guide on our website.

