



# Melville® Classic 60 Paver



- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Techniseal** 1 bag of sand covers approx. 65 ft<sup>2</sup>


## Melville® Classic 60 Paver




	DIMENSIONS (MM)	DIMENSIONS (IN)
	60 x 100 x 200	2 3/8 x 3 15/16 x 7 7/8
Weight/unit	2.8 kg	6 lb
Unit/surface	50.00 unit/m <sup>2</sup>	4.57 unit/ft <sup>2</sup>
Area/layer	1.10 m <sup>2</sup>	11.82 ft <sup>2</sup>
<b>Area/cube</b>	<b>11.00 m<sup>2</sup> 10 Rows</b>	<b>118.20 ft<sup>2</sup></b>
Qty/cube	540 units	540 units
Length/row Soldier	5.50 lin. m	18.05 lin. ft
Length/cube Soldier	55.00 lin. m	180.50 lin. ft
Weight/cube	1549 kg	3420 lb

CODE 10509003 COLOUR Grey


Sold by layer  
Can be double stacked  
Production location Montréal




### LAYING PATTERNS




Parquet Pattern



Herringbone



Herringbone 45°



Linear

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville Classic 60 Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.