



# Versailles® Slab




	Dimensions mm	Dimensions in.
	50 x 610 x 610	2 x 24 x 24
Weight/unit	44 kg	97 lb
Unit/area	0.37 m <sup>2</sup>	4.00 ft <sup>2</sup>
Area/cube	7.43 m <sup>2</sup>	80.00 ft <sup>2</sup>
<b>Qty/cube</b>	<b>20 units</b>	<b>20 units</b>
Weight/cube	880 kg	1940 lb

Code	Colour
	<b>Standard</b>
12059261	Alpine Grey
12059263	Trenton Grey
Sold by piece	
Production location Montreal	

### Typical Row



### Laying Pattern



Checkerboard

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Versailles Slab</b>	CSA A231.1	±4.5 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Compatible with pedestal systems.