





# Grande Smooth Wall *New*




375 Standard	Dimensions mm	Dimensions in.
	200 x 375 x 1000	7 7/8 x 14 3/4 x 39 3/8
Weight/unit	161 kg	360 lb
Area/layer	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
Area/cube	1.80 m <sup>2</sup>	19.56 ft <sup>2</sup>
Length/cube	9.00 lin. m	29.60 lin. ft
<b>Qty/cube</b>	<b>9 units</b>	<b>9 units</b>
Weight/cube	1500 kg	3300 lb


Code	Colour
129000448	Grey
<b>Standard</b>	
Sold by piece	
Can be double stacked	
Production location Quebec	




750 Standard	Dimensions mm	Dimensions in.
	200 x 750 x 1000	7 7/8 x 29 1/2 x 39 3/8
Weight/unit	328 kg	726 lb
Area/layer	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
Area/cube	0.80 m <sup>2</sup>	8.70 ft <sup>2</sup>
Length/cube	4.00 lin. m	13.10 lin. ft
<b>Qty/cube</b>	<b>4 units</b>	<b>4 units</b>
Weight/cube	1350 kg	2970 lb

Code	Colour
129000449	Grey
<b>Standard</b>	
Sold by piece	
Can be double stacked	
Production location Quebec	



1125 Standard	Dimensions mm	Dimensions in.
	200 x 1125 x 1000	7 7/8 x 44 5/16 x 39 3/8
Weight/unit	483 kg	1065 lb
Area/layer	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>
Area/cube	0.60 m <sup>2</sup>	6.45 ft <sup>2</sup>
Length/cube	3.00 lin. m	9.90 lin. ft
<b>Qty/cube</b>	<b>3 units</b>	<b>3 units</b>
Weight/cube	1450 kg	3190 lb



Code	Colour
129000452	Grey
<b>Standard</b>	
Sold by piece	
Can be double stacked	
Production location Quebec	







TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Smooth Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>2</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

# Grande Smooth Wall

Corner Unit	Dimensions mm		Dimensions in.		Code	Colour	Typical Row
	200 x 500 x 1000		7 7/8 x 19 11/16 x 39 3/8		Standard		
	Weight/unit	213 kg	469 lb		129000451	Grey	
	Unit/area	3.33 units/m <sup>2</sup>	0.31 unit/ft <sup>2</sup>		Call for custom colour information		
	<b>Qty/cube</b>	<b>6 units*</b>	<b>6 units*</b>		Sold by piece		
	Weight/cube	1278 kg	2811 lb		Can be double stacked		
	* 6 units equal: 3 right units, 3 left units						
Production location Quebec							

Step 175	Dimensions mm		Dimensions in.		Code	Colour	Typical Row
	175 x 438 x 1000		6 7/8 x 17 1/4 x 39 3/8		Standard		
	Weight/unit	175 kg	386 lb		129000453	Grey	
	Length/cube	1.20 lin. m	19.68 lin. ft		Sold by piece		
	<b>Qty/cube</b>	<b>6 units</b>	<b>6 units</b>		Can be double stacked		
	Weight/cube	1070 kg	2358 lb		Production location Quebec		
Production location Quebec							

Capping 438	Dimensions mm		Dimensions in.		Code	Colour	Typical Row
	200 x 438 x 1000		7 7/8 x 17 1/4 x 39 3/8		Standard		
	Weight/unit	194 kg	427 lb		129000450	Grey	
	Unit/area	5.00 units/m <sup>2</sup>	0.46 unit/ft <sup>2</sup>		Sold by piece		
	<b>Qty/cube</b>	<b>6 units</b>	<b>6 units</b>		Can be double stacked		
	Weight/cube	1162 kg	2561 lb		Production location Quebec		
Production location Quebec							

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Smooth Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm