

Agora Aqua Paver




ASTM #8 Aggregate
jointing material



Light
Commercial



| | Dimensions mm | Dimensions in. |
|--------------------|----------------------------|------------------------------------|
| A | 80 x 167 x 300 | 3 1/8 x 6 9/16 x 11 |
| B | 80 x 200 x 300 | 3 1/8 x 7 7/8 x 11 |
| C | 80 x 233 x 300 | 3 1/8 x 9 3/16 x 11 |
| Weight/unit (avg.) | 11 kg | 24 lb |
| Unit/area (avg.) | 13.27 units/m ² | 1.51 units/ft ² |
| Area/layer | 0.86 m ² | 9.26 ft ² |
| Area/cube | 6.88 m² | 8 Rows 74.08 ft² |
| Length/row | 4.20 lin. m | 13.78 lin. ft |
| Length/cube | 33.60 lin. m | 110.24 lin. ft |
| Weight/cube | 1265 kg | 2789 lb |



Colour

Standard


Rockland Black

Range Amber Beige

Range Shaded Grey

Range Scandina Grey

A, B, C are sold together



| | Dimensions mm | Dimensions in. |
|------------------------|----------------------------|-----------------------------------|
| Large Rectangle | 80 x 233 x 300 | 3 1/8 x 9 3/16 x 11 |
| Weight/unit (avg.) | 13 kg | 28 lb |
| Unit/area (avg.) | 14.28 units/m ² | 1.33 units/ft ² |
| Area/layer | 0.98 m ² | 10.55 ft ² |
| Area/cube | 7.84 m² | 8 Rows 84.40ft² |
| Length/row | 4.20 lin. m | 13.78 lin. ft |
| Length/cube | 33.60 lin. m | 110.24 lin. ft |
| Qty/cube | 112 units | 112 units |
| Weight/cube | 1440 kg | 3175 lb |



Colour

Standard


Rockland Black

Range Amber Beige

Range Shaded Grey


Range Scandina Grey

A, B, C are sold together



Make sure that when using mixed bundle, Large Rectangle will be required to fill voids

Laying Pattern



Linear

TECHNICAL INFORMATION

| Product | Standard | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|-------------------------|------------|-------------------|----------------------|--|---------|------------|--|
| Agora Aqua Paver | CSA A231.2 | N/A | μ 50 MPa ≥ 45 MPa | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles | N/A | N/A | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Joint spacing is 7 mm (0.28 in.) which allows an initial surface infiltration rate of +/- 13 300 mm/hr.

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.