



Metrik™ Slab




	Dimensions mm	Dimensions in.
	60 x 70 x 280	2 3/8 x 2 3/4 x 11
Weight/unit	2.7 kg	5.96 lb
Area/unit	0.02 m ²	0.21 ft ²
Area/layer	0.92 m ²	9.95 ft ²
Area/cube	11.09 m²	12 Rows
		119.40 ft²
Qty/cube	576 units	576 units
Weight/cube	1558 kg	3434 lb

Code	Colour	Typical Row
Prestige		
10502884	Blizzard (2)	
10502882	Rockland Black (1)	
127000940	Range Scandina Grey (1) - <i>N</i>	
Sold in full cubes only Can be double stacked Production locations: Cambridge (1) Montreal (2)		


Laying Patterns




Checkerboard



Offset 1/2



Offset 1/3



Herringbone

1 bag of sand covers approx. 55 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Metrik Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.