


Mondrian® Plus 60 Small Rectangle Paver




| | Dimensions mm | Dimensions in. |
|------------------|----------------------------|----------------------------|
| | 60 x 330 x 165 | 2 3/8 x 13 x 6 1/2 |
| Weight/unit | 7.7 kg | 17 lb |
| Unit/area | 18.52 units/m ² | 1.71 units/ft ² |
| Area/layer | 0.82 m ² | 8.79 ft ² |
| Area/cube | 9.84 m² | 12 Rows |
| Length/row | 4.95 lin. m | 16.25 lin. ft |
| Length/cube | 59.43 lin. m | 195.00 lin. ft |
| Qty/cube | 180 units | 180 units |
| Weight/cube | 1389 kg | 3062 lb |


| Code | Colour |
|----------------------------|-----------------|
| | Prestige |
| 12052557 | Rockland Black |
| Sold in full cubes only | |
| Production location Bolton | |



Laying Patterns



Linear



Herringbone

Techniseal 1 bag of sand covers approx. 38 ft²

TECHNICAL INFORMATION

| Product | Standard | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|---|------------|-------------------|----------------------|--|---------|------------|--|
| Mondrian Plus 60 Small Rectangle Paver | CSA A231.2 | N/A | μ 50 MPa ≥ 45 MPa | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles | N/A | N/A | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.
The Mondrian Plus 60 Slab is compatible with the Mondrian Plus 60 small rectangle paver for non-vehicular application only.