



Mondrian® Plus 80 Paver




	Dimensions mm	Dimensions in.
A	80 x 165 x 330	3 1/8 x 6 1/2 x 13
B	80 x 330 x 330	3 1/8 x 13 x 13
C	80 x 330 x 495	3 1/8 x 13 x 19 1/2
Weight/unit (avg.)	18 kg	40 lb
Unit/area (avg.)	9.17 units/m ²	0.85 unit/ft ²
Area/layer	0.98 m ²	10.55 ft ²
Area/cube	8.82 m²	9 Rows 94.95 ft²
Qty/cube	A = 36 B = 36 C = 18	
Length/row	2.97 lin. m	9.75 lin. ft
Length/cube	26.73 lin. m	87.75 lin. ft
Weight/cube	1680 kg	3704 lb

Code	Colour
Prestige	
10551159	Range Margaux Beige
10551158	Range Amboise Beige
10550461	Range Scandina Grey
Standard	
10551156	Range Norvick Grey
10551160	Range Newport Grey


Sold in full cubes only
Can only be stacked 3 pallets high
Production location Bolton



Laying Patterns



Linear



Modular

Techniseal 1 bag of sand covers approx. 43 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 80 Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient: 126 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).