


# Trafalgar® 60 Paver




		Dimensions mm	Dimensions in.
A	A	60 x 100 x 200	2 3/8 x 3 15/16 x 7 7/8
	B	60 x 200 x 200	2 3/8 x 7 7/8 x 7 7/8
	C	60 x 300 x 200	2 3/8 x 11 13/16 x 7 7/8
B	Weight/unit (avg.)	12.51 kg	27.60 lb
	Unit/area (avg.)	23.96 units/m <sup>2</sup>	2.32 units/ft <sup>2</sup>
	Area/layer	0.96 m <sup>2</sup>	11.63 ft <sup>2</sup>
	<b>Area/cube</b>	<b>10.56 m<sup>2</sup></b>	<b>10 Rows 116.30 ft<sup>2</sup></b>
C	Qty/cube	A = 80 B = 80 C = 100	
	Length/row	5.40 lin. m	17.72 lin. ft
	Length/cube	54.01 lin. m	177.20 lin. ft
	Weight/cube	1466 kg	3209 lb

Code	Colour
	<b>Prestige</b>
10550442	Range Margaux Beige
	<b>Standard</b>
10550368	Range Norvick Grey
10550370	Range Newport Grey
Sold in full cubes only	
Production location Woodstock	


### Typical Row



### Laying Patterns



Linear



Modular

1 bag of sand covers approx. 122 ft<sup>2</sup>

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Trafalgar 60 Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient: 484 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).