


# Vendome® 60 and 80 Paver



**60 mm**  
Not  
vehicular




	Dimensions mm	Dimensions in.
A	60 x 130 x 197	2 3/8 x 5 1/8 x 7 3/4
B	60 x 130 x 262	2 3/8 x 5 1/8 x 10 5/16
C	60 x 130 x 327	2 3/8 x 5 1/8 x 12 7/8
Weight/unit (avg.)	4 kg	8.5 lb
Unit/area (avg.)	30.50 units/m <sup>2</sup>	2.83 units/ft <sup>2</sup>
Area/layer	1.05 m <sup>2</sup>	11.28 ft <sup>2</sup>
<b>Area/cube</b>	<b>8.40 m<sup>2</sup></b>	<b>8 Rows 90.24 ft<sup>2</sup></b>
Length/row	8.19 lin. m	26.87 lin. ft
Length/cube	65.52 lin. m	214.96 lin. ft
Weight/cube	1013 kg	2233 lb


Code	Colour
	<b>Prestige</b>
10554763	Rockland Black
10554761	Range Margaux Beige
	<b>Standard</b>
10554762	Range Newport Grey

Sold in full cubes only  
Production location Bolton

**Typical Row**



**80 mm**




	Dimensions mm	Dimensions in.
A	80 x 130 x 197	3 1/8 x 5 1/8 x 7 3/4
B	80 x 130 x 262	3 1/8 x 5 1/8 x 10 5/16
C	80 x 130 x 327	3 1/8 x 5 1/8 x 12 7/8
Weight/unit (avg.)	6 kg	12 lb
Unit/area (avg.)	30.50 units/m <sup>2</sup>	2.83 units/ft <sup>2</sup>
Area/layer	1.05 m <sup>2</sup>	11.28 ft <sup>2</sup>
<b>Area/cube</b>	<b>8.40 m<sup>2</sup></b>	<b>8 Rows 90.24 ft<sup>2</sup></b>
Qty/cube	A = 88    B = 96    C = 72	
Length/row	7.86 lin. m	25.80 lin. ft
Length/cube	62.90 lin. m	206.40 lin. ft
Weight/cube	1468 kg	3236 lb


Code	Colour
	<b>Prestige</b>
10550002	Rockland Black
10559011	Range Margaux Beige
	<b>Standard</b>
10559010	Range Newport Grey

Sold in full cubes only  
Production location Bolton


**Typical Row**



## Laying Patterns



Linear



Modular

Techniseal® 1 bag of sand covers approx. : Vendome 60 - 44 ft<sup>2</sup> / Vendome 80 - 33 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Vendome Paver</b>	CSA A231.2	N/A	µ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient: 890 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).