

# Leno Capping




## Bullnose



	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
<b>Qty/cube</b>	<b>24 units</b>	<b>2 Rows</b>
Weight/cube	925 kg	2038 lb

Code	Colour
<b>Standard</b>	
121000134	Range Amber Beige
10502415	Range Shaded Grey
10502416	Range Scandina Grey
10502414	Rockland Black
Sold by piece	
Production location St-Eustache	

## Typical Row



## Straight


*New*



	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
<b>Qty/cube</b>	<b>24 units</b>	<b>2 Rows</b>
Weight/cube	925 kg	2038 lb

Code	Colour
<b>Standard</b>	
121000141	Range Amber Beige
121000139	Range Scandina Grey
121000138	Rockland Black
Sold by piece	
Production location St-Eustache	

## Typical Row



## Lafitt


*New*



	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
<b>Qty/cube</b>	<b>24 units</b>	<b>2 Rows</b>
Weight/cube	925 kg	2038 lb

Code	Colour
<b>Standard</b>	
121000137	Range Margaux Beige
121000136	Range Newport Grey
121000135	Rockland Black
Sold by piece	
Production location St-Eustache	

## Typical Row



## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Leno Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m <sup>3</sup>	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm