



# Melville® 60 and Melville® 60 DuraFusion Slabs




|  | Dimensions mm      | Dimensions in.             | Code                       | Colour                       | Typical Row |  |
|--|--------------------|----------------------------|----------------------------|------------------------------|-------------|--|
|  | A                  | 60 x 190 x 380             | 2 3/8 x 7 1/2 x 15         |                              |             |  |
|  | B                  | 60 x 380 x 380             | 2 3/8 x 15 x 15            |                              |             |  |
|  | C                  | 60 x 380 x 570             | 2 3/8 x 15 x 22 7/16       |                              |             |  |
|  | Weight/unit (avg.) | 19 kg                      | 42 lb                      |                              |             |  |
|  | Unit/area (avg.)   | 0.14 unit/m <sup>2</sup>   | 1.46 units/ft <sup>2</sup> |                              |             |  |
|  | Area/layer         | 1.08 m <sup>2</sup>        | 11.66 ft <sup>2</sup>      |                              |             |  |
|  | <b>Area/cube</b>   | <b>10.80 m<sup>2</sup></b> | <b>10 Rows</b>             | <b>116.60 ft<sup>2</sup></b> |             |  |
|  | Qty/cube           | 80 units                   | 80 units                   |                              |             |  |
|  | Weight/cube        | 1538 kg                    | 3391 lb                    |                              |             |  |
|  |                    |                            |                            | <b>DuraFusion</b>            |             |  |
|  |                    |                            | 12051953                   | Marbella                     |             |  |
|  |                    |                            | 12051954                   | Silverstone                  |             |  |
|  |                    |                            | 12051955                   | Hickory                      |             |  |
|  |                    |                            | <b>Prestige</b>            |                              |             |  |
|  |                    |                            | 12053046                   | Range Amber Beige            |             |  |
|  |                    |                            | 12052734                   | Range Margaux Beige          |             |  |
|  |                    |                            | 12052104                   | Range Chambord Grey          |             |  |
|  |                    |                            | 12052365                   | Range Scandina Grey          |             |  |
|  |                    |                            | 12052732                   | Rockland Black               |             |  |
|  |                    |                            | <b>Standard</b>            |                              |             |  |
|  |                    |                            | 12053045                   | Range Shaded Grey            |             |  |
|  |                    |                            | 12052733                   | Range Newport Grey           |             |  |

Sold by layer  
 Can be double stacked  
 Production locations:  
 DuraFusion - Metcalfe  
 Prestige and Standard - Montreal, Quebec and Metcalfe

## Laying Patterns



Modular



Linear

1 bag of sand covers approx. 155 ft<sup>2</sup>

## TECHNICAL INFORMATION

| Product                 | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability  | Density | Absorption | Dimension Tolerance*   |
|-------------------------|------------|-------------------|----------------------|--|---------|------------|--|
| <b>Melville 60 Slab</b> | CSA A231.1 | ±4.5 MPa          | N/A                  | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.