



Melville® 80 and Melville® 80 DuraFusion Pavers




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	A	80 x 190 x 380	3 1/8 x 7 1/2 x 15		
	B	80 x 380 x 380	3 1/8 x 15 x 15		
	C	80 x 380 x 570	3 1/8 x 15 x 22 7/16		
	Weight/unit (avg.)	27 kg	59 lb		
	Unit/area (avg.)	7.39 units/m ²	0.69 unit/ft ²		
	Area/layer	1.08 m ²	11.66 ft ²		
	Area/cube	8.64 m²	8 Rows	93.28 ft²	
	Length/row	3.04 lin. m	9.97 lin. ft		
	Length/cube	24.32 lin. m	79.79 lin. ft		
	Weight/cube	1716 kg	3783 lb		

DuraFusion	
10554893	Marbella
10555066	Silverstone
10555067	Hickory
Prestige	
10550869	Range Amber Beige
10550447	Range Margaux Beige
10554764	Range Chambord Grey
10550446	Range Scandina Grey
10550557	Rockland Black
Standard	
10550868	Range Shaded Grey
10550558	Range Newport Grey




Sold by layer
Production locations:
DuraFusion - Metcalfe
Prestige and Standard - Montreal, Quebec and Metcalfe

Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 116 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 and DuraFusion Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.