


# Melville® 80 Small Rectangle Paver




Pavers




	Dimensions mm	Dimensions in.
	80 x 190 x 380	3 1/8 x 7 1/2 x 15
Weight/unit	14 kg	30 lb
Unit/area	13.89 units/m <sup>2</sup>	1.29 units/ft <sup>2</sup>
Area/layer	0.87 m <sup>2</sup>	9.33 ft <sup>2</sup>
<b>Area/cube</b>	<b>7.83 m<sup>2</sup></b>	<b>9 Rows</b>
		<b>83.97 ft<sup>2</sup></b>
Length/layer	4.57 lin. m	15.00 lin. ft
Length/cube	41.15 lin. m	135.00 lin. ft
Qty/cube	108 units	108 units
Weight/cube	1465 kg	3225 lb

Code	Colour
	<b>Prestige</b>
10550871	Range Amber Beige
10551033	Rockland Black
10551031	Range Scandina Grey
	<b>Standard</b>
10550870	Range Shaded Grey


Sold by layer  
Can be double stacked  
Production location Montreal and Quebec



## Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 77 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville 80 Small Rectangle Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.