


Mondrian® Plus 60 Slab




		Dimensions mm	Dimensions in.
A	A	60 x 165 x 330	2 3/8 x 6 1/2 x 13
	B	60 x 330 x 330	2 3/8 x 13 x 13
B	C	60 x 330 x 495	2 3/8 x 13 x 19 1/2
	Weight/unit (avg.)	14 kg	30 lb
C	Area/unit	0.11 m ²	1.17 ft ²
	Area/layer	0.98 m ²	10.55 ft ²
	Area/cube	11.76 m²	12 Rows
	126.60 ft²		
Qty/cube	A = 48	B = 48	C = 24
Weight/cube	1666 kg	3667 lb	


Code	Colour
Prestige	
12052893	Range Margaux Beige
12052894	Range Amboise Beige
12052566	Range Scandinia Grey
Standard	
12052891	Range Norvick Grey
12052892	Range Newport Grey
Sold by layer	
Can be double stacked	
Production location Montreal, Quebec and St-Eustache	




Laying Patterns



Linear
100% Mix A, B, C



Modular
100% Mix A, B, C



Modular
100% Mix A, B, C

1 bag of sand covers approx. 57 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.