



# Virage Paver




	Dimensions mm	Dimensions in.
	80 x 300 x 300	3 1/8 x 11 7/8 x 11 7/8
Weight/unit (avg.)	16 kg	36 lb
Unit/area (avg.)	11.41 units/m <sup>2</sup>	1.06 units/ft <sup>2</sup>
Area/layer	1.05 m <sup>2</sup>	11.32 ft <sup>2</sup>
<b>Area/cube</b>	<b>8.41 m<sup>2</sup></b>	<b>8 Rows</b>
Length/row	3.55 lin. m	11.65 lin. ft
Length/cube	28.42 lin. m	93.23 lin. ft
Weight/cube	1548 kg	3413 lb

Code	Colour
	<b>Prestige</b>
10303063	Range Scandinia Grey
Sold by layer	
Production location Cambridge	


### Typical Row




## Laying Patterns




Beaded pattern




Circle pattern




Link pattern



Mosaic pattern



Random pattern



Wave pattern

## TECHNICAL INFORMATION

Product	Standard	Void Opening	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Virage Paver</b>	CSA A231.2	47%	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).